

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ENOVALITE

Supplier's address: ENOVATEK GmbH, Sillensteder Straße 213, 26441 Jever, DE

Model identifier: ELED400161

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	150	Energy efficiency class	D
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	23 250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	150,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	262	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	225	
	Depth	225	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,373 0,371
Parameters for LED and OLED light sources:			
R9 colour rendering index value	9	Survival factor	-
the lumen maintenance factor	-		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)-: not applicable;

(b)-: not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: x=0.3725 y=0.3708/u'=0.2222 v'=0.4978
 CCT=4183K (Duv=-0.0004) Dominant WL:Ld =578.6nm WL:Lc = --nm Purity=23.1%
 Ratio:R=17.7% G=78.8% B=3.5% Peak WL:Lp=449.2nm FWHM=22.2nm
 Render Index:Ra=82.2

R1 =81 R2 =87 R3 =92 R4 =82 R5 =81 R6 =82 R7 =86
 R8 =66 R9 =9 R10=69 R11=81 R12=61 R13=82 R14=95 R15=75

Photo Parameters:

Flux = 23727 lm Eff. : 0.00 lm/W Fe = 72.68 W
 Scotopic:40549 S/P:1.709


Electrical parameters:

V = 6.8443 V I = 0 A P = 0 W PF = 0
 LEVEL:OUT WHITE:ANSI_4000K

Status: Integral T = 4 ms Ip = 34897 (53%)

Tester:DAMIN Number:2
 Date:2023-04-07 15:09:29
 Temperature:25.3Deg Humidity:65.0%
 Manufacturer:0 Remarks:0.646A 232.2V 150W

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: x=0.3725 y=0.3708/u'=0.2222 v'=0.4978
 CCT=4183K (Duv=-0.0004) Dominant WL:Ld =578.6nm WL:Lc = --nm Purity=23.1%
 Ratio:R=17.7% G=78.8% B=3.5% Peak WL:Lp=449.2nm FWHM=22.2nm
 Render Index:Ra=82.2

R1 =81 R2 =87 R3 =92 R4 =82 R5 =81 R6 =82 R7 =86
 R8 =66 R9 =9 R10=69 R11=81 R12=61 R13=82 R14=95 R15=75

Photo Parameters:

Flux = 23727 lm Eff. : 0.00 lm/W Fe = 72.68 W
 Scotopic:40549 S/P:1.709


Electrical parameters:

V = 6.8443 V I = 0 A P = 0 W PF = 0
 LEVEL:OUT WHITE:ANSI_4000K

Status: Integral T = 4 ms Ip = 34897 (53%)

Tester:DAMIN Number:2
 Date:2023-04-07 15:09:29
 Temperature:25.3Deg Humidity:65.0%
 Manufacturer:0 Remarks:0.646A 232.2V 150W

Model placed on the Union market from 11/04/2023



EPREL registration number: 1552895

<https://eprel.ec.europa.eu/qr/1552895>

Supplier: ENOVATEK GmbH (Importer)

Website: www.enovatek.de

Customer care service:

Name: ENOVATEK GmbH

Website: www.enovatek.de

Email: info@enovatek.de

Phone: +49 4461 / 7464233

Address:

Sillensteder Straße 213

26441 Jever

Germany