

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LUXULA

**Supplier's address:** ENOVATEK GmbH, Sillensteder Straße 213, 26441 Jever, DE

**Model identifier:** LX500101

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD 2835		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	150	Energy efficiency class	E
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	18 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	5 000
On-mode power ( $P_{on}$ ), expressed in W	150,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,50
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	260	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	260	
	Depth	128	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,345 0,355
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	80	Survival factor	-
the lumen maintenance factor	-		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)-: not applicable;

(b)-: not applicable;

# Spectrum Test Report

## Product Information


Product Type: LX500101  
Product Number: 1

Product Spec: 5000K

## CIE Colorimetric Parameters

Chromaticity coordinates:  $x=0.3426$   $y=0.3587$   $u(u')=0.2070$   $v=0.3252$   $v'=0.4877$   
CCT:  $T_c=5121K$  ( $duv=0.00456$ ) Color Ratio: R=0.150 G=0.809 B=0.042  
Peak Wavelength: 0nm Half Bandwidth: 19.8nm  
Dominant Wavelength: 567.9nm Color Purity: 0.105  
CRI: Ri: Ra= 81.8

R1 =81	R2 =82	R3 =82	R4 =88	R5 =81	R6 =75	R7 =90	R8 =75
R9 =12	R10=56	R11=87	R12=49	R13=80	R14=90	R15=77	



## Photometric Parameters

Luminous Flux: 17883.0 lm Efficiency: 118.3lm/W

## Electric Parameters


Voltage: 230.32V Current: 0.6610A Power: 151.175W  
Power Factor: 0.993 Frequency: 50.00Hz

## Test Information

Scan Range: 380nm~800nm:1nm  
Stabilization Time: 0 Min  
Max of Signal: 12604 (37474)

Photometric Method:  
Photometric Condition: Sphere diameter: 1.00m, 4π  
CCD Integration Time: 69.88 ms

Model placed on the Union market from 03/04/2023



**EPREL registration number:** 1546488

<https://eprel.ec.europa.eu/qr/1546488>

**Supplier:** ENOVATEK GmbH (Importer)

**Website:** [www.enovatek.de](http://www.enovatek.de)

**Customer care service:**

**Name:** ENOVATEK GmbH

**Website:** [www.enovatek.de](http://www.enovatek.de)

**Email:** [info@enovatek.de](mailto:info@enovatek.de)

**Phone:** +49 4461 / 7464233

**Address:**

Sillensteder Straße 213

26441 Jever

Germany