

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUXULA

Supplier's address: ENOVATEK GmbH, Sillensteder Straße 213, 26441 Jever, DE

Model identifier: LX400112

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD 2835		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	100	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	10 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	100,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	274	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	218	
	Depth	28	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,380 0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value	80	Survival factor	-
the lumen maintenance factor	-		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)-: not applicable;

(b)-: not applicable;

Lightsource Test Report

Product Information

Product Type: LX400112
Product Number: 5

Product Spec: 4000K


CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.3751$ $y=0.3722$ $u(u')=0.2233$ $v=0.3325$ $v'=0.4988$
 CCT: $T_c=4119K$ ($duv=-0.00052$) Color Ratio: $R=0.179$ $G=0.789$ $B=0.032$
 Peak Wavelength: 449.3nm Half Bandwidth: 17.6nm
 Dominant Wavelength: 578.9nm Color Purity: 0.243
 CRI: $R_a=81.5$ TM30: $R_f=79$, $R_g=97$

R1 =80	R2 =86	R3 =91	R4 =82	R5 =80	R6 =81	R7 =86	R8 =66
R9 =8	R10=67	R11=80	R12=55	R13=82	R14=95	R15=75	

 Color Quality Scale: $Q_a=80.7$, $Q_f=80.4$, $Q_p=82.0$, $Q_g=94.0$

Q1 =83	Q2 =98	Q3 =74	Q4 =72	Q5 =79	Q6 =81	Q7 =83	Q8 =88
Q9 =96	Q10=85	Q11=82	Q12=82	Q13=82	Q14=72	Q15=76	



Photometric Parameters

Luminous Flux: 8968.84 lm Efficiency: 90.05 lm/W Radiant Power: 27.194 W
 EEI: 0.15 Energy Efficiency Class: A+ (EU 874-2012)

Electric Parameters

Voltage: 230.90V Current: 0.4350A Power: 99.60W
 Power Factor: 0.9910 Frequency: 50.00Hz


Test Information

Scan Range: 380~800:1nm	Photometric Method: sphere-spectroradiometer
Stabilization Time: 0 ms	Photometric Condition: Sphere diameter: 1.00m, 4π
Max of Signal: 21025 (37369)	CCD Integration Time: 52.23 ms

Condition: $T_x:0.0^\circ C$, $T_i:0.0^\circ C$, R.H.:60%
 Test Lab:
 Operator:

Test Device: Inventive CMS-2S (Plus)
 Test Time:
 Inspector:

Model placed on the Union market from 03/04/2023



EPREL registration number: 1545784

<https://eprel.ec.europa.eu/qr/1545784>

Supplier: ENOVATEK GmbH (Importer)

Website: www.enovatek.de

Customer care service:

Name: ENOVATEK GmbH

Website: www.enovatek.de

Email: info@enovatek.de

Phone: +49 4461 / 7464233

Address:

Sillensteder Straße 213

26441 Jever

Germany